

## TECHNICAL DATA SHEET

**PRODUCT NAME : *MB BI 60 AT A***

Form :	[ Pellet ]	Carrier :	[ LLDPE ]
Melt Temperature (°C) :	[ 125 ]	Resin Suitability:	[ PP, PE ]
Let Down (%) :	[ 2-5 ]	Melt Flow Index (g/10mins):	[ ≤4.7 ]
Water Ratio (%) :	[ ≤0.30 ]	Movability Resistance (level):	[ 5 ]
Heat Stability (°C) :	[ 300 ]	Heat Resistance (level):	[ 5 ]
Specific Gravity (g/cm <sup>3</sup> ) :	[ 1.56 ]	Light Fastness (level):	[ 7 ]
Bulk Density g/cm <sup>3</sup> ) :	[ 1.35 ]	Main Application:	Extrusion, Injection, Blowing

### MAIN COMPOSITON

Total pigment equivalent is 60% ± 3%

### HEALTH AND SAFETY

Confirm with the European Resolution AP 89 (1) heavy metal content.

### PACKAGING

*MB BI 60 AT A* is packed in 25 kg bags. Please store in the dry place.

### REMARKS

PE – PP, for film colouring, bottles, drums, sheets, pipes, large garbage cans, trash and garbage bags, housewares etc.